

Material Handling – Drum Master

Leveling Jacks



Our Zinc Plated Levelizing Jacks have a divided housing with flange plates for bolting above and below frame of equipment. Units have a capacity of 5,000 lbs. For raising, leveling, and Stabilizing Portable Equipment.

	Min. Extd. Height	Max. Extd. Height	Overall Height	Screw Travel	Net Weight (lbs)
	4½"	13½"	18"	9"	13
	4½"	21½"	26"	17"	15
	4½"	25½"	30"	21"	16

Material Handling – Drum Master

Floor Locks



Push down pedal for automatic locking

Lift with toe to unlock

Approximately one inch ground clearance

Model	Mounting Height	Retracted Height	Used With Caster Size	Net Weight (lbs)
	5-5/8"	4-11/16"	4"	9
	5-13/32"	4-11/16"	4"	9
	7-1/4"	6-1/4"	6"	12
	7-3/4"	6-3/4"	8"	19
	9-15/16"	8-7/8"	8"	19
	7-3/8"	4-1/8"	6"	12

Floor Lock Top Plate Measurements

Model	Bolt Hole Spacing	Mounting Bolt Size	Overall Plate Size	Thickness of Plate
	2-5/8"x3-5/8"	3/8"	3-11/16"x5-3/8"	3/8"
	2-5/8"x3-5/8"	3/8"	3-11/16"x5-3/8"	3/8"
	2-7/16"x4-15/16"	1/2"	4-1/2"x6"	7/16"
	2-7/16"x4-15/16"	1/2"	4-1/2"x6"	7/16"
	3-3/8"x5-1/4"	1/2"	5-3/8"x7-1/4"	3/8"
	2-7/16"x4-15/16"	3/8"	4-1/2"x6-1/2"	3/16"