



## ▼ **HB-ES800C**

Motor power:500W/800W  
Battery:lead acid battery,12A/12V\*3PCS  
Loading capacity:65kgs  
Max Speed:30km/h  
Charging time:6-8hours  
Braking system(F/R):disc brake  
Transmission system:chain  
Tire:250-10"  
G.W/N.W:38/33kgs  
Conveyance:336pcs/40' HQ

## ▲ **HB-GS02F**

Engine: 49cc, single cylinder,2-stroke, air-cooled  
Ignition: CDI  
Start-up: pull  
Drive system: chain-driving  
Tire: 10"  
Front and rear disc brakes  
Fuel tank: 1.5L  
Fuel/Oil Ratio: 25:1  
Speed: 45mph  
Run distance: 30km per tank  
Conveyance: Qty/40' HQ: 440 units





## ◀ **HB-GS05J**

Engine type: 4-Stroke 200cc, air cooled.

4-Stroke 150cc, air cooled.

Bore & Stroke: 63.5 x 62.2 mm (200cc) 62 x 49.5 mm (150cc)

Starter: kick+electric or kick start

Compression: 9.2:1

Transmission: 5-speed (1-0-2-3-4-5), International gear

Max Power: 10.8/8000 (1 ± 5%) ((200cc);

9.3/8500 (1 ± 5%) ((150cc))

Front shock: reversed front hydraulic shock

Rear shock: hydraulic shock

Brakes: disc brake

Front&rear wheel: Front 17inch; Rear 14inch

Front&rear wheel: Front 19inch; Rear 16inch are also available

Engine color: black is available

Package Size: 157 x 37 x 79cm

Conveyance: 132pcs/40HQ

## ▶ **HB-GS05**

Engine Type: 125cc, 4 Strokes,  
Single Cylinder, and Air Cooled

Start mode: Kick Start

Start mode: Kick & Electric Start is available

Front shock: up-down side shock

Brakes: disc/disc (F/R)

Front & Rear wheel: 14 inch/12 inch

Front & Rear wheel: 17 inch/14 inch is available

Conveyance: 199pcs/40HQ/195pc/40HQ





## ◀ **HB-GS05A**

Engine Type: 125cc, 4 Strokes,  
Single Cylinder, and Air Cooled  
Start mode: Kick Start  
Start mode: Kick & Electric Start is available  
Front shock: up-down side shock  
Brakes: disc/disc (F/R)  
Front & Rear wheel: 14 inch/12 inch  
Front & Rear wheel: 17 inch/14 inch is available  
Conveyance: 199pcs/40HQ/195pc/40HQ

## ▶ **HB-GS05F**

Engine Type: 125cc, 4 Strokes,  
Single Cylinder, and Air Cooled  
Start mode: Kick Start  
Start mode: Kick & Electric Start is available  
Compression Ratio: 9.7: 1  
Max power: 8.5kw/9500rpm  
Front shock: up-down side shock  
Brakes: disc/disc (F/R)  
Front & Rear wheel: 14 inch/12 inch  
Conveyance: 172pcs/40HQ







## ◀ **HB-GS02C**

Engine: 49cc, single cylinder, 2-stroke, air-cooled

Ignition: CDI

Start-up: pull

Drive system: chain-driven

Tire: 12"

Front and rear disc brakes

Fuel tank: 1.5L

Fuel/Oil Ratio: 25:1

Speed: 45mph

Run distance: 30km per tank

Product size: 108x25x76cm

Seat height: 54cm

Max load: 120kg

N.W.: 22kg G.W.: 24kg

QTY:40'HQ:480pcs





## ◀ **HB-PSB01**

Engine: 49CC, single-cylinder,  
air-cooled, 2-stroke

Max speed: 50km/h

Start way: pulling start

Tire: 11"

Front and rear brake: disc brake

Tank capacity: 1.5L

Drive system: chain

Distance per tank: 50km/h

Colors option: black, red, blue, yellow,  
silver and assorted color

Conveyance: Qty/40HQ":370pcs

